IP Link® Device Interface Communication Sheet

This document provides additional assistance with wiring your Extron IP Link enabled product to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific Extron IP Link enabled product or the controlled device manufacturer supplied documentation.

Device Specifications:

Device Type: Switcher
Manufacturer: Atlona
Firmware Version: N/A
Model(s): AT-HD-V81

Version History:

Driver Version	Date	IP Link Compiler	GC Version	Notes
1	11/17/2011	1.4.0	3.2.0	Initial version.

Driver Notes:

Control Commands & States:

Input	1 to 8	
Power Control	On	Off
Signal Enhance	On	Off

Status Available: N/A

MLC62 Supported Commands:

Input	1 to 8	
Power Control	On	Off
Signal Enhance	On	Off

Cable and Adapter Requirements:

M/F RS-232 straight serial cable (Extron Electronics P/N 26-433-XX)

Notes for the Device:

Serial communication:

Port Type:	RS-232	**Parity:**	None
Baud Rate:	9600	**Stop Bits:**	1
Data Bits:	8	**Flow Control:**	None

Pin Assignments Diagram:



RS232 DB9 Male
IP Link® Device Interface



Signal	Pin	Main Cable	Pin	Signal
RxD	2	←	2	TxD
TxD	3	→	3	RxD
GND	5	—	5	GND



RS232 DB9, Female
Adapter

Note: Captive screw connector may also be used as a serial connection.

General Notes: